

Date:

Coverage area:

Thickness:

Number of bags used:

Installed by:




**International Cellulose Corp.**

12315 Robin Blvd.  
Houston, TX 77045

Celbar Loosefill Insulation has been installed to an

**R-**



Call for you local contractor  
800-444-1252 / 713-433-6701

1.6 PCF R VALUE	MINIMUM SETTLED THICKNESS	INITIAL INSTALLED INCHES	MINIMUM BAGS PER 1000 SQ FT		MAX COVERAGE PER BAG (SQ FT)		MINIMUM POUNDS	
			NET	GROSS	NET	GROSS	NET AREA	GROSS
			35 LBS	35 LBS	35 LBS	35 LBS	NET AREA	2 x 6 JOIST
13	3.8	4.40	15	13	69	76	0.51	0.46
19	5.6	6.50	21	19	47	52	0.75	0.68
22	6.5	7.25	25	23	41	44	0.86	0.8
30	8.8	10.00	34	32	30	32	1.18	1.11
38	11.2	12.25	43	41	23	25	1.49	1.42
49	14.4	15.75	55	53	18	19	1.92	1.85

**In determining initial installed thickness, the following equipment was utilized:  
Ranger 5 L/S, Air Setting was 12, Material Feed Gate was 3.**

### Read this before you buy What you should know about R-values

The chart shows the R-value of this insulation. R means the resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are others factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings will depend upon the climate, the type of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-value it is essential that this insulation is properly installed.