



R A N G E R L S / 5 0 0

SPECIFICALLY DESIGNED FOR THE APPLICATION OF CELBAR WALL-SPRAY

INCLUDES :

- ◆ Ranger LS/500
- ◆ 3" x 50' fiber hose, 3/pkg.
- ◆ 7-2.5" Hose Clamps
- ◆ Remote Control with 200' extension
- ◆ 9 GPM pump assembly with 2-hp/220v motor
- ◆ 1/2" x 200' 600 psi liquid line with fittings
- ◆ Inlet filter assembly
- ◆ Reducer & clamps
- ◆ 2.5 x 50 fiber hose, 1pkg.
- ◆ Fiber grate



R A N G E R L / S 5 0 0

A L L O W S :

- ◆ Increased capacity
- ◆ On-site training
- ◆ Two man operation
- ◆ Variable speed
- ◆ Professional wall Spray

RANGER L/S 500 NEW FEATURES:

- ◆ Improved spray applications
- ◆ High production capabilities
- ◆ Reduces nozzle plugs
- ◆ New filters with increased surface area
- ◆ 300' plus blowing hose capacity

Electrical Components

- ◆ Separate electrical and mechanical compartments
- ◆ Push Button on & off controls
- ◆ Upgraded electrical components
- ◆ CE Compliant

Other Features

- ◆ Versatile wall-spray system
- ◆ Dependable
- ◆ Fast cleanup
- ◆ Simple operation
- ◆ Low maintenance

STANDARD FEATURES:

- ◆ All-welded structural steel construction
- ◆ Variable feed rate w/indicator
- ◆ 8" wheels for easy mobility
- ◆ 2-bag hopper capacity
- ◆ Size: 38"L x 24"W x 48"H
- ◆ Weight: 350 lbs.
- ◆ Passes through standard doorways
- ◆ 1.5hp TEFC 220v/60hz single phase motor
- ◆ Operates on 30 amp circuit
- ◆ Push-to-reset breakers
- ◆ Digital volt and hour meters
- ◆ AR-200 power receptacle
- ◆ Boost transformer
- ◆ Accessory parts available-in stock

**CALL TODAY!
800/444-1252**



International Cellulose Corporation

P.O. BOX 450006 ♦ HOUSTON, TX 77245 ♦ 713/433-6701 ♦ 713/433-2029 FAX ♦ www.spray-on.com

Prices and specifications subject to change without notice. © International Cellulose Corporation 05/03